



技术参数:

插芯:

- 插针数: 8/0+PE
 - 额定电流: 100A
 - 额定电压: 690V
 - 额定脉冲电压: 8kV
 - 污染等级: 3
 - 依据UL额定电压: 600V
 - 依据UL额定电流: 82A
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: >500
- 插针:
- 接线方式: 轴向螺钉连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $<0.5\text{m}\Omega$
 - 线径范围: $10-25\text{mm}^2(7-3 \text{ AWG})$
 - 最大绝缘直径: 11.4mm
 - 拧紧力矩:
 - mm^2 : 10 16 25
 - N·m: 6 6 7
 - 剥线长度: $13^{\pm 1}$
 - 内角扳手: SW-4*100

Technical specification:

Insters:

- No. of contact: 8/0+PE
 - Rated current: 100A
 - Rated voltage: 690V
 - Rated impulse voltage: 8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL: 600V
 - Rated current acc.to UL: 82A
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: >500
- Contacts:
- Terminal: axial screw terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $<0.5\text{m}\Omega$
 - Wire gauge: $10-25\text{mm}^2(7-3 \text{ AWG})$
 - Stripping length: 11.4mm
 - Tightening torque:
 - mm^2 : 35 50 70
 - N·m: 8 9 10
 - Stripping length: $13^{\pm 1}$
 - Tools:
 - Hexagonal driver: SW-4*100

					表面处理 Finish	-			图号 Drawing No.	-	
					材料 Material	-			产品代号 Part Code	HK-008/0-M	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date				产品料号 Part No.	2120082101	
		姓名/Name	日期/Date	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn			18.10.2010	标准化 Stand.	-	2:3	V1.0	39g	-		
审核 Checked			18.10.2010								
工艺 Process				批准 Approved							
						All Dimensions in mm Original Size DIN A 4			浙江西霸士电气有限公司		