



技术参数:

- 模块数量: 6
- 接地线:
  - 功率线: 4-10mm<sup>2</sup>(12-8 AWG)
  - 信号线: 1-2.5mm<sup>2</sup>(18-14 AWG)
- 材料: 压铸铝
- 温度范围: -40℃ - +125℃
- 可插拔次数: ≥500

Technical specification:

- No. of module: 6
- Wire gauge(PE contact):
  - Power side: 4-10mm<sup>2</sup>(12-8 AWG)
  - Signal side: 1-2.5mm<sup>2</sup>(18-14 AWG)
- Material: zinc die-cast
- Temperature range: -40℃ - +125℃
- Mating cycles: ≥500

					表面处理 Finish	-				图号 Drawing No.	-
					材料 Material	-				产品代号 Part Code	HF24B-NLA.6
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	2070244102
绘图 Drawn	姓名/Name	日期/Date	姓名/Name	日期/Date	产品名称 Part Name					-	
审核 Checked		06.03.2017	标准化 Stand.	-	-	2:3	V1.0	64g	-		
工艺 Process	-	-	批准 Approved		06.03.2017	All Dimensions in mm Original Size DIN A 4			浙江西霸士电气有限公司		