



技术参数:

- 模块数量: 3
- 接地线:
  - 功率线: 4-10mm<sup>2</sup>(12-8 AWG)
  - 信号线: 1-2.5mm<sup>2</sup>(18-14 AWG)
- 材料: 压铸锌
- 温度范围: -40℃ - +125℃
- 可插拔次数: ≥500

Technical specification:

- No. of module: 3
- Wire gauge(PE contact):
  - Power side: 4-10mm<sup>2</sup>(12-8 AWG)
  - Signal side: 1-2.5mm<sup>2</sup>(18-14 AWG)
- Material: zinc die-cast
- Temperature range: -40℃ - +125℃
- Mating cycles: ≥500

				表面处理 Finish		-		图号 Drawing No.	-
				材料 Material		-		产品代号 Part Code	HF10B-UA.3
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date			产品料号 Part No.	2070104001
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.
绘图 Drawn		06.03.2017	标准化 Stand.	-	-	1:1	V1.0	64g	-
审核 Checked		06.03.2017						产品名称 Part Name	-
工艺 Process	-	-	批准 Approved		06.03.2017			All Dimensions in mm Original Size DIN A 4	
								浙江西霸士电气有限公司	